

DESKTOP LABEL MACHINE

LC 2112A

- Laminating/Die cutting/Wasting/Slitting/Rewinding in one machine.
- Supporting self-developed Cutstudio software, generate marker points with one click, automatically extract cut profiles.
- High-definition LCD seven-inch touch screen Human-computer interaction is more convenient.
- LiDAR rangefinder monitors material status in real time.
- Free slitting: Automatic correction.
- Digital intelligent slitting.



Integration
process



Intelligent
operation



Save space



Multiple
connection



Slitting



Die cutting



Wasting



HEFEI SAGA COMPUTER NUMERICAL CONTROL Co.,Ltd.

☎ Tel: +86-551-63444544

📍 Address: Block7 Liando U-valley, Jilin Crossing of
Fanhua Avenue, Baohe District, Hefei, Anhui Province, PRC



Website



WeChat

PRODUCT PARAMETERS:

Model		LC 2112A
Motor		X-Servo motor
Sensor		Y-Servo motor
Control panel		CCD camera
Number of tool holders		7 inch touchscreen
Blade types		1
		Graver/pen
Function		
Functions		Dot mark+QR code
Scan marks		Laminating/Die cutting/Slitting/Wasting
Scan marks speed		About 5S
Cutting speed		15-1050
Cutting force		0-750
Minimum character	About 5mm ² (Depend on variable material and graphics)	
Maximum diameter of paper feed roll		350mm
Maximum diameter of film roll		150mm
Maximum diameter of waste roll		300mm
Maximum diameter of paper receiving roll		300mm
Maximum label width		330mm
Maximum label length		270mm
Minimum label length		20mm
Slitting width		Minimum 10mm
Slitting blades		Standard 6 knives
Slitting speed		3meters /minute
Slitting accuracy		±0.5mm
Mechanical resolution		0.02mm
Programmable resolution		HPGL0.025mm
Repeat precision		≤0.05mm
Programmable resolution		Roll coated paper、sticker ect
Software and compitability		
Connect		USB interface、Net interface、U disk and WiFi
Software and compitability		Cutstudio software Corel Draw plugin and Illustrator plugin
Power and environment		
Voltage		100VAC-120VAC,50/60Hz,Max8A 200VAC-240VAC,50/60Hz,Mini4A
Power		Max 350W
Operation environment		Temperature +5℃ to +35 ℃ (Fahrenheit 41-95), Humidity 30% -75% (Non-condensing)
Dimensions and Weight		
Actual dimensions		L 1086mm×W 819mm×H 1320mm
Package dimensions		L 1245mm×W 945mm×H 1525mm

This parameter is subject to change without prior notice. The company reserves the right of final interpretation

APPLICABLE MATERIALS:

Ordinary Sticker

Special Sticker

PVC

PET

APPLICATION DISPLAY :

